

Technical Specification



Product Code: CHPPR2

Description: 2 Channel Programmer



General Information

Dimensions Display

Heating System

Clock

140mm x 88.6mm x 32.1mm Backlit LCD 12 hour am/pm, 1 minute resolution, accuracy +/- 1.5 sec/day Gravity or Pumped

BACKLIT

DISPLAY

CE

UK

Power

Operating Voltage 230V AC, 50Hz Battery Type Lithium Cell CR1225 IEC Protection Class Class II

Construction

Material ABS Wiring Fixed wiring only

Outputs

230VAC (Switched Live) 2 x 2(1)A

Programming

Programming Schedule 24 Hour, 5/2 Day and 7 Day Programmable Available Operations 2 or 3 ON/OFF Periods Modes Available On, Off, Auto, All Day Pre-Programmed Schedule Yes Summer/Winter Time Yes; Automatic Change Holiday Mode Yes With/without Service Optional Setting Interval Function **Boosts** Selectable Durations 1,2 or 3 Hour Boost Environment

Ingress Protection IP30 Operating Temperature 0°C to 40°C

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 E: info@espuk.com | W: espuk.com

Page 1 of 1 Rev.1 Errors & Omissions excluded. Specification is subject to change without notice.