



**TITLE:**

Alarm TCCA Type 3 PVC

**CODE:**

SFX/6C-TY3-PVC-WHT-100




**DESCRIPTION:**

100m 6 Core TCCA Type 3 Alarm Cable  
White PVC

**SUPPLIED AS:**

Reel of 100m

- Generally used for connecting alarm equipment such as sensors, control panels and other low voltage circuits
- This cable is ROHS compliant
- Polyvinyl chloride plastic has excellent aging properties and will usually exceed a 25-30 year service life
- This is the most popular and cost effective cable for general intruder alarm solutions
- Improved performance and protection against fire



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23



## Product Specification



### Cable Construction

|                          |                                   |
|--------------------------|-----------------------------------|
| Cable Construction       | 6 Cores                           |
| CPR                      | Eca                               |
| Conductor                | Tinned Copper Clad Aluminium      |
| Conductor Diameter (mm)  | 0.20 ±0.008 x 7                   |
| Stranded Diameter (mm)   | 0.22                              |
| Overall Diameter (mm)    | 4.00 ±0.200                       |
| Compliance and Standards | BS4737-3.30:2015,RoHS2 2011/65/EU |

### Insulation

|                             |                                    |
|-----------------------------|------------------------------------|
| Insulation                  | PVC                                |
| Insulation Colour           | Red,Black,Blue, Yellow,Green,White |
| Insulation Resistance @20°C | >200 MO/km                         |
| Insulation Thickness (mm)   | 0.21                               |

### Outer/Jacket Specification

|                       |                |
|-----------------------|----------------|
| Jacket                | PVC            |
| Overall Colour        | White          |
| Overall Diameter (mm) | 4.00 ±0.200    |
| Jacket Colour         | White RAL 9003 |
| Jacket Thickness (mm) | 0.5            |
| Nylon Rip-Cord        | Yellow 210D    |

### Electrical Characteristics

|                                    |               |
|------------------------------------|---------------|
| Insulation Resistance @20°C        | >200 MO/km    |
| Max Conductor DC resistance @ 20°C | 155O/km       |
| Rated Temperature (°C)             | -20°C to 80°C |
| Rated Voltage (V)                  | 30V           |






## MORE INFORMATION:

| EURO CLASS<br>(ca:cable)         | CLASSIFICATION CRITERIA   |  | CPR GUIDE   | Securi-Flex®  |
|----------------------------------|---|--|---|---|
|                                  | FIRE RATING   | SFX COMMENT  |   |   |
| Reaction to Fire BS EN ISO 1716  |   |  | SUBCLASSIFICATIONS FOR EUROCLASSES B <sub>ca</sub> to D <sub>ca</sub>   |   |
| <b>A<sub>ca</sub></b>            | Does not contribute to the fire                                       | Due to availability, it will be almost impossible for a cable to meet A <sub>ca</sub> , so they should only be specified with extreme caution.   | <b>(S) SMOKE PRODUCTION</b>   | <b>(D) FLAMING DROPLETS</b>   |
| Reaction to Fire BS EN 50399     |   |  | BS EN 50399/BS EN 61034-2   | BS EN 50399   |
| <b>B1<sub>ca</sub></b>           | Minimum contribution to the fire                                      | It's highly unlikely the commonly-used cables will be classified to Class B1 <sub>ca</sub> .   | s1a: s1 + transmittance >=80% (BS EN 61034-2)   | d0: No fall of droplets or flaming particles, times for 1200 seconds                                    |
| <b>B2<sub>ca</sub></b>           | Combustible, low flame spread & heat release contribution to the fire | Similar to Class C <sub>ca</sub> , although a lower acceptable heat release rate and burn measurement. In practice, this is likely to be the highest class cables will meet.   | s1b: s1 + transmittance >=60% <80% (BS EN 61034-2)  | d1: Fall of droplets or flaming particles that persist for less than 10 seconds, timed for 1200 seconds |
| <b>C<sub>ca</sub></b>            | Combustible, moderate flame spread & heat release                     | This is a more rigorous test than Class D <sub>ca</sub> , this is widely accepted across Europe as the 'go to' classification, but be aware, many cables do not meet Class C <sub>ca</sub> though availability is improving. | s1: Low production of slow propagation of smoke   | a1: Very low acidity (conductivity <2.5 µS/mm & pH >4.3)  |
| <b>D<sub>ca</sub></b>            | Combustible, moderate flame spread & heat release                     | This classification has relatively little use or acceptance within specifying/contracting organisations. This is because no large scale fire growth is measured.   | s2: Intermediate production & propagation of smoke  | a2: low acidity (conductivity <10 µS/mm & pH >4.3)  |
| Reaction to Fire BS EN 60332-1-2 |   |  | s3: None of the above   | d2: None of the above   |
| <b>E<sub>ca</sub></b>            | Combustible, limited fire spread of less than 425mm                   | A basic test for vertical flame propagation for a single insulated wire or cable using a 1 KW pre-mixed flame. Note: This test does not measure heat release, toxic fumes or smoke.  | Visit us online: <a href="http://www.securiflex.co.uk">www.securiflex.co.uk</a> The Trusted Cable Brand   |   |
| <b>F<sub>ca</sub></b>            | Combustible, fire spread of more than 425mm                           | Cables classified to Class F <sub>ca</sub> may have high levels of flammability due to the materials they are made of. This does not mean that the cable cannot be used, it is more likely to be used external.              | Classes A to E have to be tested by an independent authorised laboratory. Most cables will fall into classes B2 <sub>ca</sub> to E <sub>ca</sub> . For a cable to meet A <sub>ca</sub> , B1 <sub>ca</sub> , B2 <sub>ca</sub> or C <sub>ca</sub> , there also needs to be regular on-going factory audits. |   |

## OUR OPERATING TEMPERATURE RANGE GUIDE



enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23